



SOUTH FLORIDA WATER MANAGEMENT DISTRICT

FORM 60
Oct. 1977

WELL LOG

WELL LOCATION

County Broward (Collier Manor)

Station I. D. 011000002

Date 8/7/78 Well No. Collier Manor No. 2

Latitude 26° 06' 10" Longitude 80° 07' 50"

NW ¼ SW ¼ NW ¼ Section 30 Township 48S Range 42E

Owner Broward Utilities Phone _____

Driller Alsay Pippin Date Drilled 1967

WELL CONSTRUCTION

Drilling Method: Rot. Air CT Auger Other _____

T. Depth - Driller 1153' T. Depth - Logger 992.0'

Casing Depth Driller 999.0' Casing Depth Logger 976.5'

Bit Size _____ Casing Dia. I.D. _____

Hole Dia. 16" From 0.0' To 290' Dia. 10" From 0.0" To 976.5'

Type of Casing steel Casing Thickness _____

Type of Screen open hole Screen Int. From _____ To _____

Type of Packing none Well Use injection (abandoned)

Static Water Level _____ Date _____

Yield Flow _____ Pump _____

DATUM

K.B. _____ L.S. 14.7' T.O.C. 18.7'

FLUID QUALITY

Date 8/7/78 Time 1015 Source of Sample wellhead

Cl _____ mg/l Type of Fluid water

Temp. 26.2 °C Field Density _____ @ _____ °C

T.D.S. _____ mg/l Spec. Cond. 1200 µmhos/cm

Logged By: M. P. Brown Witnessed By: G. Paluga

Comments: Electric logs should not be used quantitatively

Location - lat. and long. approximate

Depth scale referenced to TOC as 0.0'

TYPE OF SURVEYS RUN

Lateral 6'	()	Density	()
Caliper	()	ccl	()
Flow meter	()	Fluid Sampler	()
16", 64" normals	(X)	Temperature	()
Neutron	()	Delta Temp.	()
Natural Gamma	()	SP	()
Fluid Resistivity	()		

