

All interpretations are opinions based on inferences from electrical or other measurements and we cannot and do not guarantee the accuracy or correctness of any interpretation and we shall not be liable for any loss, cost, damages or expenses incurred or sustained by anyone resulting from any interpretation made by any of our officers, agents or employees. These interpretations are also subject to our general terms and conditions set forth in our current Price Schedule.

Comments

DILLA1SSP
FCT
FVCGR
FLOWMETER

Database File: Resync2.db
Dataset Pathname: run4:EIDWCMP1
Presentation Format: Mar_psp
Dataset Creation: Mon Nov 10 10:18:44 2008 by Log Open Caswell 070914
Charted by: Depth in Feet scaled 1:240

0 Gamma Ray (api) (GAPI) 100
10 CALX (in) 30
240 DT (usec/ft) (usec/ft) 40
100 Sonic Porosity (DTMAA=47.6) (psi) (psi 0
900
950
1000
1050
1100
1150
1200
1250
Gamma Ray
Caliper Average Caliper (in)
Sonic Delta Time
Sonic Porosity (DTMAA=47.6) (psi) (psi)

Database File: Resync2.db
Dataset Pathname: run4:EIDWCMP1
Presentation Format: Mar_psp
Dataset Creation: Mon Nov 10 10:18:44 2008 by Log Open Caswell 070914
Charted by: Depth in Feet scaled 1:240

0 Gamma Ray (api) (GAPI) 100
10 CALX (in) 30
240 DT (usec/ft) (usec/ft) 40
100 Sonic Porosity (DTMAA=47.6) (psi) (psi 0
900
950
1000
1050
1100
1150
1200
1250
Gamma Ray
Caliper Average Caliper (in)
Sonic Delta Time
Sonic Porosity (DTMAA=47.6) (psi) (psi)

Database File: Resync2.db
Dataset Pathname: run4:EIDWCMP1
Presentation Format: Mar_psp
Dataset Creation: Mon Nov 10 10:18:44 2008 by Log Open Caswell 070914
Charted by: Depth in Feet scaled 1:240

0 Gamma Ray (api) (GAPI) 100
10 CALX (in) 30
240 DT (usec/ft) (usec/ft) 40
100 Sonic Porosity (DTMAA=47.6) (psi) (psi 0
900
950
1000
1050
1100
1150
1200
1250
Gamma Ray
Caliper Average Caliper (in)
Sonic Delta Time
Sonic Porosity (DTMAA=47.6) (psi) (psi)

Database File: Resync2.db
Dataset Pathname: run4:EIDWCMP1
Presentation Format: Mar_psp
Dataset Creation: Mon Nov 10 10:18:44 2008 by Log Open Caswell 070914
Charted by: Depth in Feet scaled 1:240

0 Gamma Ray (api) (GAPI) 100
10 CALX (in) 30
240 DT (usec/ft) (usec/ft) 40
100 Sonic Porosity (DTMAA=47.6) (psi) (psi 0
900
950
1000
1050
1100
1150
1200
1250
Gamma Ray
Caliper Average Caliper (in)
Sonic Delta Time
Sonic Porosity (DTMAA=47.6) (psi) (psi)

Database File: Resync2.db
Dataset Pathname: run4:EIDWCMP1
Presentation Format: Mar_psp
Dataset Creation: Mon Nov 10 10:18:44 2008 by Log Open Caswell 070914
Charted by: Depth in Feet scaled 1:240

0 Gamma Ray (api) (GAPI) 100
10 CALX (in) 30
240 DT (usec/ft) (usec/ft) 40
100 Sonic Porosity (DTMAA=47.6) (psi) (psi 0
900
950
1000
1050
1100
1150
1200
1250
Gamma Ray
Caliper Average Caliper (in)
Sonic Delta Time
Sonic Porosity (DTMAA=47.6) (psi) (psi)

Database File: Resync2.db
Dataset Pathname: run4:EIDWCMP1
Presentation Format: Mar_psp
Dataset Creation: Mon Nov 10 10:18:44 2008 by Log Open Caswell 070914
Charted by: Depth in Feet scaled 1:240

240 Sonic Delta Time (usec/ft) 40
10 Caliper Average (in) (in) 30
400 SSVF4 1400
900
950
1000
1050
1100
1150
1200
1250
Sonic Delta Time
Caliper Average (in) (in)

240 Sonic Delta Time (usec/ft) 40
10 Caliper Average (in) (in) 30
400 SSVF4 1400

ALLWIRES

REPEA PASS

Database File: Resync2.db
Dataset Pathname: run4:EIDWC
Presentation Format: Mar_psp
Dataset Creation: Mon Nov 10 10:00:20 2008 by Log Open Caswell 070914
Charted by: Depth in Feet scaled 1:240

240 Sonic Delta Time (usec/ft) 40
10 Caliper Average (in) (in) 30
400 SSVF4 1400
1100
1150
1200
1250
Sonic Delta Time
Caliper Average (in) (in)

240 Sonic Delta Time (usec/ft) 40
10 Caliper Average (in) (in) 30
400 SSVF4 1400

Sensor	Offset (ft)	Schematic	Description	Len (ft)	OD (in)	Wt (lb)
			CHD-SSVCHD (SDD)	1.00	1.50	5.00
			CBLINLINE	3.00	1.50	10.00
SSVF1 SSVF2	7.25 7.25		SLTCPulse-Probe(TS/Probe (1)	8.83	2.75	100.00
SSVF3 SSVF4	4.25 4.25					
			CBLINLINE	3.00	1.50	10.00

Dataset Resync2.db: RebSvfnetfield(EIDWCMP1
Total Length 10.83 ft
Total Weight 127.00 lb
O.D. 2.75 in