

**Schlumberger Well Surveying Corporation**  
**LATER LOGGING**  
 071-33

COMPANY: EVERETT OIL AND REFINING COMPANY  
 WELL: CONSOLIDATED BAVA  
 STORE-STATE #1  
 FIELD: WILDOAT  
 LOCATION: SEC-16-46E-27E  
 COUNTY: LEE  
 STATE: FLORIDA

Location of Well: 1011' S & 1783' E  
 C of NW/COOR SEC: 46243  
 Elevation: D.F. 46.50  
 K.S. 28  
 or O.L. 27.50  
 FILING No.:

RUN No. ONE TWO  
 Date: 8-15-58 11-21-58  
 First Reading: 4278 11905  
 Last Reading: 1208 7278  
 Feet Measured: 1210 7278  
 Csg. Schum.: 1208 4312  
 Csg. Driller: 1208 4308  
 Depth Reached: 4482 11910  
 Bottom Driller: 4500 11878  
 Depth Datum: ONE FOOT ABOVE BENTONITE  
 Mud Not. CLEAR WATER - LIME BASE  
 Density: 10.3  
 Viscosity: 48  
 Resist. 6" 7.0 48 12.7  
 Resist. BHT 6" 7.0 28 12.7  
 pH: 6.5 12.8  
 Wtr. Lost: 0.32 ml. 2.5 C. 22 ml.  
 Max. Temp.: 114 110  
 Bit Size: 1 1/8" 5/8"

Dr. Rig Time: 3 HRS 4 HRS  
 Truck No.: 7773  
 Recorded by: GILLIOTT  
 Witness: FABRACORRINTY

26 28 28 81 37 2101  
 X=296348 Y=778595  
 16-46S-27E

#189  
 CORKSCREW  
 MKR  
 RSR

L-5009

REMARKS: MEASURED VALUES CHART VALUES  
 RMP 0.18 AT 120 0.12 AT 120  
 RMC 0.36 AT 120 0.27 AT 120

NOTE: NO DETAIL LOG FURNISHED WITH ORIGINAL PRINT

NOTE: TRACED SP RUN #2 IS 100V

SP (MV)	RESISTIVITY OHMS M <sup>2</sup> /M
0	30
0	300
0	3000

