

CEMENT:ASTM TYPE II

CEMENT:ASTM TYPE II

CEMENT:ASTM TYPE II

2020 FEET  
2030 FEET

NOTE:  
8 5/8-INCH CASING  
CENTRALIZER SETTINGS.

( DEPTH IN FEET )

36
119
281
476
667
865
1052
1248
1439
1634
1862
1900
1942
1979

32.5-INCH DIAMETER HOLE.

CONDUCTOR CASING 24-INCH  
O.D. 0.375-INCH WALL  
THICKNESS.

430 FEET

435 FEET

NOMINAL 24-INCH DIAMETER  
HOLE.

INTERMEDIATE CASING 18-INCH  
O.D. 0.375-INCH WALL  
THICKNESS.

INJECTION CASING 8 5/8-INCH  
O.D. 0.50-INCH WALL  
THICKNESS, INTERNALLY  
COATED.

CENTRALIZERS  
(SEE NOTE FOR DEPTHS)

2 CEMENT BASKETS  
2011 FEET & 2014 FEET

2015 FEET

14 3/4-INCH DIAMETER  
OPEN HOLE.

2800 FEET TOTAL DEPTH

PREPARED FOR

HARRIS CORPORATION

TITLE

INJECTION WELL 2

COMPLETED CONSTRUCTION DETAILS

COMPILED BY

W. RICE

DRAWN BY

B. OLIVA

CHECKED BY

WHEATLEY

Geraghty & Miller

Ground-Water Engineers

DATE

JUNE 88

REVISED

SCALE

NONE

FIGURE 3