COMPANY	EXXON COMPANY U.S.A.
WELL	A-14 (32-06-11-16)
FIELD	PRUDHOE BAY UNIT
COUNTY	NORTH SLOPE BOROUGH
STATE	ALASKA
API NUMBER	50-029-21965-01
LOCATION	1,000' FNL & 1,000' FEL
SECTION	32
TOWNSHIP	11N
RANGE	16E
PERMANENT DATUM	MEAN SEA LEVEL
ELEV.	0 FT.
LOG MEASURED FROM	55.4 FT. ABOVE PERM. DATUM
DRILLING MEASURED FROM	RKB
ELEV. K.B.	55.4 FT.
ELEV. D.F.	54.4 FT.
ELEV. G.L.	19.4 FT.
DATE	03-MAY-96
RUN NUMBER	ONE
DEPTH DRILLER	10,500 FT.
DEPTH LOGGER	10,498 FT.
BOTTOM LOGGED INTERVAL	10,498 FT.
TOP LOGGED INTERVAL	9,000 FT.
TYPE FLUID IN HOLE	SEAWATER
SALINITY	28,000 PPM
DENSITY	8.8 LB/GAL
LEVEL	FULL
MAX REC. TEMP.	200 DEG F
LOGGING EQUIPMENT LOCATION	3-16
RECORDED BY	J. SCHWERTNER
WITNESSED BY	MARK

CSU Sperry-Sun

EXXON COMPANY U.S.A.

A-14 (32-06-11-16)

PRUDHOE BAY UNIT

NORTH SLOPE BOROUGH ALASKA

50-029-21965-01

1,000' FNL & 1,000' FEL

SECTION 32 TOWNSHIP 11N RANGE 16E

PERMANENT DATUM MEAN SEA LEVEL ELEV. 0 FT.

LOG MEASURED FROM 55.4 FT. ABOVE PERM. DATUM

DRILLING MEASURED FROM RKB

ELEV. K.B. 55.4 FT.

ELEV. D.F. 54.4 FT.

ELEV. G.L. 19.4 FT.

DATE 03-MAY-96

RUN NUMBER ONE

DEPTH DRILLER 10,500 FT.

DEPTH LOGGER 10,498 FT.

BOTTOM LOGGED INTERVAL 10,498 FT.

TOP LOGGED INTERVAL 9,000 FT.

TYPE FLUID IN HOLE SEAWATER

SALINITY 28,000 PPM

DENSITY 8.8 LB/GAL

LEVEL FULL

MAX REC. TEMP. 200 DEG F

LOGGING EQUIPMENT LOCATION 3-16

RECORDED BY J. SCHWERTNER

WITNESSED BY MARK

REMARKS

EQUIPMENT NUMBERS:

ALL INTERPRETATIONS ARE OPINIONS BASED ON INFERENCES FROM ELECTRICAL OR OTHER MEASUREMENTS AND WE CANNOT, AND DO NOT GUARANTEE THE ACCURACY OR CORRECTNESS OF ANY INTERPRETATIONS, AND WE SHALL NOT, EXCEPT IN THE CASE OF GROSS OR WILLFUL NEGLIGENCE ON OUR PART, BE LIABLE OR RESPONSIBLE FOR ANY LOSS, COSTS, DAMAGES OR EXPENSES INCURRED OR SUSTAINED BY ANYONE RESULTING FROM ANY INTERPRETATION MADE BY ANY OF OUR OFFICERS, AGENTS OR EMPLOYEES. THESE INTERPRETATIONS ARE ALSO SUBJECT TO OUR GENERAL TERMS AND CONDITIONS AS SET OUT IN OUR CURRENT PRICE SCHEDULE.

CP 36.4 FILE 3 03-MAY-96 10:05

	TENSILE
10,498	BD (IN) 36.000
10,450	CD (IN) 36.000
10,400	CS (IN) 36.000

GR (GAPI) 100.00

CP 36.4 FILE 2 03-MAY-96 10:03

FT/100'

	TENSILE
10,498	BD (IN) 36.000
10,450	CD (IN) 36.000
10,400	CS (IN) 36.000

GR (GAPI) 100.00

CP 36.4 FILE 1 03-MAY-96 10:01

FT/100'

	TENSILE
10,498	BD (IN) 36.000
10,450	CD (IN) 36.000
10,400	CS (IN) 36.000

GR (GAPI) 100.00

CP 36.4 FILE 4 03-MAY-96 15:49

FT/100'

	TENSILE
10,498	BD (IN) 36.000
10,450	CD (IN) 36.000
10,400	CS (IN) 36.000

GR (GAPI) 100.00

REPEAT SECTION

CP 36.4 FILE 5 03-MAY-96 15:47

FT/100'

	TENSILE
10,498	BD (IN) 36.000
10,450	CD (IN) 36.000
10,400	CS (IN) 36.000

GR (GAPI) 100.00

CP 36.4 FILE 6 03-MAY-96 15:43

FT/100'

	TENSILE
10,498	BD (IN) 36.000
10,450	CD (IN) 36.000
10,400	CS (IN) 36.000

GR (GAPI) 100.00

BEFORE SURVEY CALIBRATION SUMMARY

TIE IN POINT(MD):	10,060.00
PROGRAM FILE:	DPC 10400100
CP 36.4	05/03/96 07:11:57

BHT

CALIPER CALIBRATION SUMMARY

MEASURED	CALIBRATED	UNITS
14.00	14.00	IN
14.00	14.0	IN
14.00	14.0	IN

THIS DATA IS PRELIMINARY AND SUBJECT TO CHANGE. IT IS THE PROPERTY OF SPERRY-SUN DRILLING SERVICES AND IS NOT TO BE REPRODUCED OR DISTRIBUTED WITHOUT THEIR PERMISSION.