CEMENT BOND LOG w/ VARIABLE DENSITY LOG

Company: Florida Design Drilling Corp.
Well: PW-2
Field: Davie
County: Broward
State: Florida
Country: USA

Run 1 | Run 2 | Run 3
Permanent Datum: Ground Level | Elev.: 0 ft
Log Measured From: Kelly Bushing | 10 ft above Perm. Datum
Drilling Measured From: Kelly Bushing
Date: 07-30-12 | | |
Depth-Driller: 1240 ft | | |
Depth-Logger: 1240 ft | | |
Bottom Logged Interval: 1240 ft | | |
Top Logged Interval: 0 ft | | |
Type Fluid in Hole: Water | | |
Salinity, PPM Cl: | | |
Density: 8.33 lb/gal | | |
Level: Full | | |
Max Rec. Temperature: 85 F | | |
Equipment Number: 3 | | |
Location: Pompano Beach, FL | | |
Recorded By: Jeff Hall | | |
Witnessed By: Mr. Bill Hall | | |

Run 1: 7" Casing, 0 - 1240 ft, 26 lb/ft, Driller
Bit Size: 6.25 in
Top Log Interval: 0 ft
Bottom Log Interval: 1240 ft
Type Fluid in Hole: Water
Density: 8.33 lb/gal
Max Rec. Temperature: 85 F
Equipment Number: 3
Location: Pompano Beach, FL
Recorded By: Jeff Hall
Witnessed By: Mr. Bill Hall

Run 2: 7" Casing, 0 - 1240 ft, 26 lb/ft, Driller
Bit Size: 6.25 in
Top Log Interval: 0 ft
Bottom Log Interval: 1240 ft
Type Fluid in Hole: Water
Density: 8.33 lb/gal
Max Rec. Temperature: 85 F
Equipment Number: 3
Location: Pompano Beach, FL
Recorded By: Jeff Hall
Witnessed By: Mr. Bill Hall

Run 3: 7" Casing, 0 - 1240 ft, 26 lb/ft, Driller
Bit Size: 6.25 in
Top Log Interval: 0 ft
Bottom Log Interval: 1240 ft
Type Fluid in Hole: Water
Density: 8.33 lb/gal
Max Rec. Temperature: 85 F
Equipment Number: 3
Location: Pompano Beach, FL
Recorded By: Jeff Hall
Witnessed By: Mr. Bill Hall

Tool Model: SLT_Bond
Tool Number: 07-155 13.2012
Depth: 0 ft
Casing Diameter: 5.5 in
Spacing: 3' Spacing
Signal Zero: 6.35 mV
Calibrated Amplitude: 71.921 mV
Reading at Signal Zero: 0.109252 @ 153612 V
Reading at Free Pipe: 0.27401 @ 153686 V
Gain: 22.2526
Offset: -3.946273

Tool Model: SLT_Bond
Tool Number: 07-155 13.2012
Depth: 0 ft
Casing Diameter: 5.5 in
Spacing: 3' Spacing
Signal Zero: 6.35 mV
Calibrated Amplitude: 71.921 mV
Reading at Signal Zero: 0.109252 @ 153612 V
Reading at Free Pipe: 0.27401 @ 153686 V
Gain: 22.2526
Offset: -3.946273

Tool Model: SLT_Bond
Tool Number: 07-155 13.2012
Depth: 0 ft
Casing Diameter: 5.5 in
Spacing: 3' Spacing
Signal Zero: 6.35 mV
Calibrated Amplitude: 71.921 mV
Reading at Signal Zero: 0.109252 @ 153612 V
Reading at Free Pipe: 0.27401 @ 153686 V
Gain: 22.2526
Offset: -3.946273

All interpretations are opinions based on inferences from electrical or other measurements and we cannot and do not guarantee the accuracy or correctness of any interpretation, and we shall not, except in the case of gross or willful negligence on our part, be liable or responsible for any loss, costs, damages, or expenses incurred or sustained by anyone resulting from any interpretation made by any of our officers, agents or employees. These interpretations are also subject to our general terms and conditions set out in our current Price Schedule.

Comments

CEMENT BOND LOG was run centralized.

MAIN PASS

Database File Nibble2.db
Dataset Pathname run\CBL\MAIN
Presentation Format cbl
Dataset Creation Mon Jul 30 10:36:01 2012
Charted by Depth in Feet scaled 1:240

400 Travel Time (usec) 800
0 Amplified Amplitude (mV) 5,000
0 Amplitude (mV) 50
Variable Density 1200

7 Travel Time
7 Amplified Amplitude
VDL
CBG

REPEAT SECTION

Database File Nibble2.db
Dataset Pathname run\CBL\RPT
Presentation Format cbl
Dataset Creation Mon Jul 30 11:55:16 2012 by Log VER_5.3
Charted by Depth in Feet scaled 1:240

400 Travel Time (usec) 800
0 Amplified Amplitude (mV) 5,000
0 Amplitude (mV) 50
Variable Density 1200

7 Travel Time
7 Amplified Amplitude
VDL
CBG

Calibration Report

Database File Nibble2.db
Dataset Pathname run\Spacer5f
Dataset Creation Mon Jul 30 17:55:16 2012 by Log VER_5.3

Cement Bond Log Calibration Report

Serial Number: Bond396
Tool Model: SLT_Bond
Tool Number: 07-155 13.2012
Depth: 0 ft
Casing Diameter: 5.5 in
Spacing: 3' Spacing
Signal Zero: 6.35 mV
Calibrated Amplitude: 71.921 mV
Reading at Signal Zero: 0.109252 @ 153612 V
Reading at Free Pipe: 0.27401 @ 153686 V
Gain: 22.2526
Offset: -3.946273

Sensor	Offset (ft)	Schematic	Description	Len (ft)	OD (in)	Wt (lbs)
TT3	9.83					
MWF3	9.83		SLT-SLT_Bond (Bond396)	16.00	3.50	127.00
TT5	7.83					
MWF5	7.83					
CCL	0.67		CCL-MVGS 1.9 (RTS-CCL-1)	1.33	1.90	8.00

Dataset Total Length: 17.33 ft
Dataset Total Weight: 135.00 lb
O.D. 3.50 in

Dataset Nibble2.db: field\wellrun3\spacer5f

MV Geophysical
Company Florida Design Drilling Corp.
Well PW-2
Field Davie
County Broward
State Florida
Country USA