
MV Geophysical
Company: Florida Design Drilling Corp
Well: FS-2
Field: Pasco
County: Broward
State: Florida
Country: USA
Drilled From: Ground Level
Casing Record: 16" @ 40'
Hole Size: 12.25"
Drilling Mud Type: Bentonite
Density: 9.2 ppg
Viscosity: 40 sec
Fluid Loss: 12 cc
Source of Sample: Shaker
Rm @ Measured Temp: 1.0 @ 70°F
Rmf @ Measured Temp: 0.75 @ 70°F
Rmc @ Measured Temp: 1.25 @ 70°F
Rm @ BHT: 0.67 @ 120°F
Time Since Circulation: 12 hrs
Max Rec Temp: 120°F
Equipment Number: 1
Location: Pasco
Recorded By: Bill
Witnessed By: Mr. Hayward-Lund
DUAL INDUCTION LL3/SP
Run Number: One
Depth-Driller: 1,000'
Depth-Logger: 1,000'
Bottom Logged Interval: 1,000'
Top Logged Interval: 40'
Type Fluid in Hole: Bentonite
Salinity: 1,000 ppm
Density: 9.2 ppg
Level: Full
Max Rec Temp: 120°F
Equipment Number: 1
Location: Pasco
Recorded By: Bill
Witnessed By: Mr. Hayward-Lund