All interpretations are opinions based on inferences from electrical or other measurements and we cannot and do not guarantee the accuracy or correctness of any interpretation and we shall not, except in the case of gross or willful negligence on our part, be liable or responsible for any loss, costs, damages or expenses incurred or sustained by anyone resulting from any interpretation made by any of our officers, agents or employees. These interpretations are also subject to our general terms and conditions set out in our current price schedule.

Comments

Run 4.252 shim-in @ 83.1 deg*

Dual Induction Calibration Report

Serial Model
Surface Calibration
Downhole Cal Performed
Downhole Verification Performed

1375 DI
Initial Apr 21 11:12:29 2010
Initial Apr 21 11:04:55 2010
Initial Apr 21 11:04:55 2010

Surface Calibration

	Readings			References			Results	
Loop	Air	Loop		Air	Loop		m	b
Deep	0.050	0.845	V	0.000	400.000	mmho-m	412.956	19.912
Medium	0.038	0.736	V	0.000	464.000	mmho-m	541.120	11.040
Internal	Zero	Cal		Zero	Cal		m	b
Deep	0.071	0.756	V	0.000	400.000	mmho-m	548.977	8.358
Medium	0.060	0.736	V	0.000	464.000	mmho-m	632.408	5.000

Downhole Calibration

	Readings			References			Results	
Internal	Zero	Cal		Zero	Cal		m	b
Deep	45.036	78.3966	mmho-m	42.000	77.960	mmho-m	0.900	9.376
Medium	41.616	466.320	mmho-m	40.000	465.998	mmho-m	107.052	2.383
Shallow	0.000	0.000	Ohm-m	0.000	0.000	Ohm-m	1.000	0.000

After Survey Verification

	Readings			Targets			Results	
Internal	Zero	Cal		Zero	Cal		m	b
Deep	0.000	0.000	mmho-m	45.036	78.396	mmho-m	0.900	9.376
Medium	0.000	0.000	mmho-m	41.616	466.320	mmho-m	107.052	2.383
Shallow	0.000	0.000	Ohm-m	0.000	0.000	Ohm-m	1.000	0.000

Datum: NAD83
Grid: NAD27
Time Depth: 00:00
Tie: 0.0