YOUNGQUIST BROTHERS

Company: SEMINOLE TRIBE OF FLORIDA - HWD
Well: MW-1
Field: HOLLYWOOD SEMINOLE
County: BROWARD
State: FLORIDA
Location: API #: 42011 Twp: 50S Rge: 41E Sec: 26 Elevation: 6.00ft (GL) 0.00ft (KB) 0.00ft (DF)
Permanent Datum: GL
Log Measured From: KB
Drilling Measured From: KB
Company: SEMINOLE TRIBE OF FLORIDA - HWD
Well: MW-1
Field: HOLLYWOOD SEMINOLE
County: BROWARD
State: FLORIDA
XY CALIPER,GAMMA RAY TEMPERATURE & SP LOG
Run Number: 1
Date: 10/10/2017
Depth Driller: 240.00ft
Depth Logger: 240.00ft
Bottom Logged Interval: 240.00ft
Top Logged Interval: 0.00ft
Casing Driller: 240.00ft @ 0.00ft
Casing Logger: 240.00ft @ 0.00ft
Bit Size: 6.75in
Type Fluid: WATER
Density: 8.33lb/gal
Viscosity: 0.00s
Fluid Loss: 0.00ml
Source of Sample: PIT
Rm @ Measured Temp: 0.00ohmm @ 0.00°F
Rmf @ Measured Temp: 0.00ohmm @ 0.00°F
Rmc @ Measured Temp: 0.00ohmm @ 0.00°F
Source of Rmf and Rmc: MEASURED
Rm @ BHT: 0.00ohmm @ 0.00°F
Time Since Circulation: 0.00hr
Time on Bottom: 0.00hr
Max Recorded Temp: 0.00°F
Equipment Number: 0
Location: 0
Recorded By: 0
Witnessed By: 0

*** Data Here ***

All interpretations are opinions based on inferences from electrical or other measurements and we cannot and do not guarantee the accuracy or correctness of any interpretation, and we shall not, except in the case of gross or willful negligence on our part, be liable or responsible for any loss, costs, damages, or expenses incurred or sustained by anyone resulting from any interpretation made by any of our officers, agents or employees. These interpretations are also subject to our general terms and conditions set out in our current Price Schedule.

Comments

MAX. CALIPER ARMS-69"

ABHV CALCULATED FOR 36" CASING

YOUNGQUIST BROTHERS

MAIN PASS

Database File: hw dte stcf mw1 db
Dataset Pathname: temp/pass2
Presentation Format: grcy-abhv
Dataset Creation: Fri Dec 22 00:24:19 2017
Charted by: Depth in Feet scaled 1:240

0 GAMMA RAY (GAPI) 100
100 SP (mV) 100
ABHV (bbl) 0

40 X-CALIPER (in) 70
40 Y-CALIPER (in) 70
40 BIT SIZE (in) 70
85 TEMP (degF) 95



YOUNGQUIST BROTHERS

REPEAT PASS

Database File: hw dte stcf mw1 db
Dataset Pathname: temp/pass3
Presentation Format: grcy-abhv
Dataset Creation: Fri Dec 22 00:11:55 2017
Charted by: Depth in Feet scaled 1:240

0 GAMMA RAY (GAPI) 100
100 SP (mV) 100
ABHV (bbl) 0

40 X-CALIPER (in) 70
40 Y-CALIPER (in) 70
40 BIT SIZE (in) 70
85 TEMP (degF) 95



Calibration Report

Database File: hw dte stcf mw1 db
Dataset Pathname: temp/pass4
Dataset Creation: Fri Dec 22 00:24:19 2017

XY Caliper Calibration Report

Serial Number/Model: 4658A XYCSM
Performed: Thu Dec 21 22:36:41 2017

Ring			X Caliper		Y Caliper	
1:	10	in	803.37	cps	1811.848	cps
2:	20	in	978.587	cps	1026.52	cps
3:	30	in	1117.93	cps	1167.17	cps
4:	40	in	1259.78	cps	1319.03	cps
5:	50	in	1412.28	cps	1483.15	cps
6:		in		cps		cps
7:		in		cps		cps
8:		in		cps		cps
9:		in		cps		cps
10:		in		cps		cps

Gamma Ray Calibration Report

Serial Number: 13
Tool Model: 3.5HCH
Performed: Thu Dec 21 11:59:12 2017

Calibrator Value: 100.0 GAPI

Background Reading: 24.8 cps
Calibrator Reading: 49.0 cps

Sensitivity: 2.1234 GAPI/cps

Calibration Report

Database File: hw dte stcf mw1 db
Dataset Pathname: temp/pass5
Dataset Creation: Fri Dec 22 01:17:57 2017

Dual Induction Calibration Report

Serial-Model: 1510-C
Surface Cal Performed: Wed Oct 04 10:42:28 2017
Internals Cal Performed: Thu Dec 21 12:56:19 2017
After Survey Verification Performed: Thu Dec 21 12:56:19 2017

Surface Calibration

	Readings			References			Results	
Loop	Air	Loop		Air	Loop		m	b
Deep	-0.003	0.668	V	0.000	400.000	mmho/m	596.595	1.577
Medium	0.047	0.820	V	0.000	464.000	mmho/m	596.216	-27.866
Internal:	Zero	Cal		Zero	Cal		m	b
Deep	0.012	0.644	V	37.423	435.140	mmho/m	747.516	46.361
Medium	0.007	0.745	V	-85.434	464.772	mmho/m	745.906	-90.706

Downhole Calibration

	Readings			References			Results	
Internal:	Zero	Cal		Zero	Cal		m	b
Deep	9.078	367.026	mmho/m	-8.710	365.864	mmho/m	0.998	-0.349
Medium	24.669	415.302	mmho/m	-23.672	416.118	mmho/m	1.000	0.987
Shallow	0.018	2.564	V	1.000	140.000	Ohm-m	54.598	0.027

After Survey Verification

	Readings			Targets			Results	
Internal:	Zero	Cal		Zero	Cal		m'	b'
Deep	0.000	0.000	mmho/m	9.078	367.026	mmho/m	0.998	-0.349
Medium	0.000	0.000	mmho/m	24.669	415.302	mmho/m	1.000	0.987
Shallow	0.000	0.000	Ohm-m	1.000	140.000	Ohm-m	1.000	0.000

Spontaneous Potential Calibration Report

Serial Number: 1510
Tool Model: C
Performed: Fri Dec 22 00:10:37 2017

Gain: 10.734

Sensor	Offset (ft)	Schematic	Description	Length (ft)	O.D. (in)	Weight (lb)
			CHD-BAICHD	1.00	1.69	10.00
			GR-GROH (13)	2.75	3.50	40.00
GR	12.60					
			XYC-XYCSM (4658M)	6.60	3.50	87.00
YCAL	8.50					
XCAL	8.50					
			BARS-1.68	3.00	1.68	50.00

Dataset: hw dte stcf mw1.db: field/well/temp/pass4
Total length: 15.35 ft
Total weight: 187.00 lb
O.D.: 3.50 in