

All interpretations are opinions based on inferences from electrical or other measurements and we cannot and do not guarantee the accuracy or correctness of any interpretation, and we shall not, except in the case of gross or willful negligence on our part, be liable or responsible for any loss, costs, damages, or expenses incurred or sustained by anyone resulting from any interpretation made by any of our officers, agents or employees. These interpretations are also subject to our general terms and conditions set out in our current Price Schedule.

Comments

XY/CIGR
BHC SONIC/VDL
FLOWMETER
FCT
DHTVS

MAIN PASS

Database File: capejw1n.db
Dataset Pathname: DLMP
Presentation Format: DIL
Dataset Creation: Wed May 28 09:43:01 2008
Charted by: Depth in Feet scaled 1:600

Gamma Ray (GAPI) 200
Spontaneous Potential (mV) 200
Deep Resistivity (OHm-m) 2000
Medium Resistivity (OHm-m) 2000
Shallow Resistivity (OHm-m) 2000
Deep Induction Resistivity
Medium Induction Resistivity
Shallow Resistivity
500
550
600
650
700
750

MAIN PASS

Database File: capejw1n.db
Dataset Pathname: DLMP
Presentation Format: DIL
Dataset Creation: Wed May 28 09:43:01 2008
Charted by: Depth in Feet scaled 1:600

MAIN PASS

Database File: capejw1n.db
Dataset Pathname: DLMP
Presentation Format: DIL
Dataset Creation: Wed May 28 09:37:41 2008
Charted by: Depth in Feet scaled 1:240

REPEAT PASS

Database File: capejw1n.db
Dataset Pathname: DLRP
Presentation Format: DIL
Dataset Creation: Wed May 28 09:37:41 2008
Charted by: Depth in Feet scaled 1:240

Dual Induction Calibration Report

Serial-Model: 9252-C
Surface Cal Performed: Fri Oct 26 16:10:19 2001
Downhole Cal Performed: Wed May 28 09:32:34 2008
After Survey Verification Performed: Wed May 28 09:32:04 2008

Surface Calibration

	Readings			References			Results	
Loop:	Air	Loop		Air	Loop		m	b
Deep	-0.005	0.847	V	0.000	400.000	mmho-m	810.298	3.302
Medium	0.010	0.714	V	0.000	404.000	mmho-m	656.366	-6.261
Internal	Zero	Cal		Zero	Cal		m	b
Deep	0.009	0.841	V	0.010	397.000	mmho-m	810.374	3.164
Medium	0.010	0.710	V	-1.120	402.000	mmho-m	659.668	-5.714

Downhole Calibration

	Readings			References			Results	
Internal	Zero	Cal		Zero	Cal		m	b
Deep	5.109	400.179	mmho-m	0.729	396.690	mmho-m	0.982	3.712
Medium	1.117	478.818	mmho-m	-1.696	461.400	mmho-m	0.976	-2.786
Shallow	-1.396	-1.051		3.000	89.900	mmho-m	235.810	332.088

After Survey Verification

	Readings			Targets			Results	
Internal	Zero	Cal		Zero	Cal		mr	br
Deep	0.000	0.000	mmho-m	5.109	400.179	mmho-m	0.982	3.712
Medium	0.000	0.000	mmho-m	1.117	478.818	mmho-m	0.976	-2.786
Shallow	0.000	0.000	mmho-m	3.000	89.900	mmho-m	1.000	0.000