

All interpretations are opinions based on inferences from electrical or other measurements and we cannot and do not guarantee the accuracy or correctness of any interpretation, and we shall not, except in the case of gross or wilful negligence on our part, be liable or responsible for any loss, costs, damages or expenses incurred or sustained by anyone resulting from any interpretation made by any of our officers, agents or employees. These interpretations are also subject to our general terms and conditions set out in our current Price Schedule.

Comments

Rm=5.854 ohm-m @ 82.1 degF



Database File conv230r.db
Dataset Pathname MAIN
Presentation Format DILCSG
Dataset Creation Mon Feb 11 14:24:04 2008
Charted by Depth in Feet scaled 1:1200



Database File conv230r.db
Dataset Pathname MAIN
Presentation Format DILCSG
Dataset Creation Mon Feb 11 14:24:04 2008
Charted by Depth in Feet scaled 1:600



Database File conv230r.db
Dataset Pathname MAIN
Presentation Format DILCSG
Dataset Creation Mon Feb 11 14:24:04 2008
Charted by Depth in Feet scaled 1:240



Database File conv230r.db
Dataset Pathname REPEAT
Presentation Format DILCSG
Dataset Creation Fri Feb 15 11:05:2008
Charted by Depth in Feet scaled 1:240

Dual Induction Calibration Report

Serial-Model 5390-R
Surface Cal Performed Thu Nov 15 11:21:40 2007
Before Survey Verification Performed Thu Nov 15 11:27:50 2007
After Survey Verification Performed Thu Nov 15 11:27:50 2007

Surface Calibration

	Readings			References		Results	
Loop	Air	Loop		Air	Loop	m	b
Deep	0.050	0.640	V	0.000	400.000 mmho-m	631.771	33.646
Medium	0.001	0.732	V	0.000	454.000 mmho-m	634.715	-0.462
Internal	Zero	Cal		Zero	Cal	m	b
Deep	0.011	0.641	V	0.000	400.000 mmho-m	634.996	-7.104
Medium	0.009	0.736	V	0.000	454.000 mmho-m	520.900	5.734

Downhole Calibration

	Readings			References		Results	
Internal	Zero	Cal		Zero	Cal	m	b
Deep	26.409	396.282	mmho-m	26.130	397.096 mmho-m	0.996	0.268
Medium	-5.803	469.733	mmho-m	-6.353	467.967 mmho-m	0.997	0.565
Shallow	2.501	0.010	V	464.500	2.000 Ohm-m	197.667	15.044

After Survey Verification

	Readings			Targets		Results	
Internal	Zero	Cal		Zero	Cal	m'	b'
Deep	26.151	396.470	mmho-m	26.409	396.282 mmho-m	0.996	0.268
Medium	5.737	470.303	mmho-m	-5.803	469.733 mmho-m	0.997	-0.565
Shallow	567.956	129.961	Ohm-m	464.500	2.000 Ohm-m	1.124	142.975