Company Diversified Drilling Corp.
Well SWROW TP-229
Field Cape Coral
County Lee
State/Prov Florida

Survey Type: Dual Induction LLS
Survey Direction: Down
Survey Purpose: Primary
Survey Contractor: Diversified Drilling Corporation
Rig Name: SWROW TP 229
Logging Engineer: Stephen Rhodes
Borehole Fluid: Water
Max Temperature: 25.00 °C
Max Recorded Temperature: 25.00 °C
Equipment Serial Number: 5306-R
Top Log Interval: 0.00 ft
Bottom Log Interval: 1200.00 ft
Casing Driller Size at Depth: 8.625 @ 200.00 ft
Casing Logger Size at Depth: 8.625 @ 200.00 ft
Bit Size: 7.875 in
Type Fluid in Hole: Water
Density / Viscosity: 1.00 g/cm³ / 1.00 cP
pH / Fluid Loss: 7.00 / 0.00 cc
Source of Sample: Pit
Rm @ Measured Temp: 4.787 @ 80.1 degF
Rmf @ Measured Temp: 4.787 @ 80.1 degF
Rmc @ Measured Temp: 4.787 @ 80.1 degF
Source of Rmf / Rmc: Calculated / Calculated
Rm @ BHT: 4.787 @ 80.1 degF
Time Circulation Stopped: 14:00
Time Logger on Bottom: 14:10
Maximum Recorded Temperature: 25.00 °C
Equipment Location: Fort Myers
Recorded By: Jeff Hall
Witnessed By: Mr. Rhodes

DUAL INDUCTION LLS

Comments

Rmf=4.787 ohm-m @ 80.1 degF

All interpretations we provide based on Measured Well data but as to other measurements and as to work and do not guarantee the accuracy or correctness of any interpretation, and we shall not, except in the case of gross or willful negligence on our part, be liable or responsible for any loss, costs, damages, or expenses incurred or sustained by anyone resulting from any interpretation made by any of our officers, agents or employees. These interpretations are also subject to our general terms and conditions set out in our current Price Schedule.

MAIN PASS

Database File sccn229.db
Dataset Pathname MAIN
Presentation Format DLI2D
Dataset Creation Wed Dec 14 11:18:04 2005
Charted by Depth in Feet scaled 1:200

SP (mV) -10 10
GR (GAPI) 0 200

RSLD (Ohm-m) 0.2 2000
RILM (Ohm-m) 0.2 2000
RILD (Ohm-m) 0.2 2000

CSG @ 200



MAIN PASS

Database File sccn229.db
Dataset Pathname MAIN
Presentation Format DLI2D
Dataset Creation Wed Dec 14 11:18:04 2005
Charted by Depth in Feet scaled 1:600

SP (mV) -10 10
GR (GAPI) 0 200

RSLD (Ohm-m) 0.2 2000
RILM (Ohm-m) 0.2 2000
RILD (Ohm-m) 0.2 2000



MAIN PASS

Database File sccn229.db
Dataset Pathname MAIN
Presentation Format DLI2D
Dataset Creation Wed Dec 14 11:18:04 2005
Charted by Depth in Feet scaled 1:240

SP (mV) -10 10
GR (GAPI) 0 200

RSLD (Ohm-m) 0.2 2000
RILM (Ohm-m) 0.2 2000
RILD (Ohm-m) 0.2 2000



REPEAT SECTION

Database File sccn229.db
Dataset Pathname REPEAT
Presentation Format DLI2D
Dataset Creation Wed Dec 14 10:25:16 2005
Charted by Depth in Feet scaled 1:240

SP (mV) -10 10
GR (GAPI) 0 200

RSLD (Ohm-m) 0.2 2000
RILM (Ohm-m) 0.2 2000
RILD (Ohm-m) 0.2 2000



Dual Induction Calibration Report

Serial-Model 5306-R
Surface Cal Performed Sun Jan 16 21:49:43 2005
Downhole Cal Performed Wed Dec 14 10:25:16 2005
After Survey Verification Performed Wed Dec 14 11:35:46 2005

Surface Calibration

	Readings			References		Results	
Loop:	Air	Loop		Air	Loop	m	b
Deep	0.050	0.648	V	0.000	400.000 mmho-m	671.771	-33.640
Medium	0.001	0.730	V	0.000	464.000 mmho-m	634.716	-0.462
Internal:	Zero	Cal		Zero	Cal	m	b
Deep	0.011	0.641	V	0.000	400.000 mmho-m	634.566	-7.104
Medium	-0.009	0.736	V	0.000	464.000 mmho-m	620.900	5.734

Downhole Calibration

	Readings			References		Results	
Internal	Zero	Cal		Zero	Cal	m	b
Deep	27.170	399.937	mmho-m	29.130	387.036 mmho-m	0.996	1.539
Medium	4.468	467.425	mmho-m	4.414	457.136 mmho-m	0.997	2.030
Shallow	0.503	0.819	Ohm-m	0.500	2.000 Ohm-m	1.000	0.221

After Survey Verification

	Readings			Targets		Results	
Internal	Zero	Cal		Zero	Cal	m'	b'
Deep	28.254	398.978	mmho-m	27.771	386.937 mmho-m	0.996	1.539
Medium	4.466	467.425	mmho-m	4.414	457.136 mmho-m	0.997	2.030
Shallow	494.948	1.814	Ohm-m	494.556	2.000 Ohm-m	0.999	0.189