

Sec. 3 TWP 47 Rge 38

Elankes
Webb Inc.

ESTABLISH Ref Elev for Newer INSTALLED
MONITORING WELLS for G-330E @ STA 2

HTA	+	HT.1.	-	Elev	Remarks
BM G-330E	4.63 9.02	23.777		19.147	FND
G-330E HTW WELLS			0.85 12.80	22.927	
G-330E HTW WELLS			3.43 10.22	20.347	
G-330E HTW	3.54 10.11	23.887			
G-330E HTW			0.965 12.685	22.922	
BM G-330E			4.7A 9.91	19.147	(19.147)

Sec. 11 TWP 23 Rge 28

Elankes
Horan

Establish Ref Elev for GW#2, Verify
Ref Elev for GW1 @ TURLAK,
Orange County.

STA	+	HT.1.	-	Elev	Remarks
BM Turlak 2008	4.87 8.78	129.15		124.28	FND.
TURLAK GW 1			2.02 11.63	127.13	
TURLAK GW 2			2.09 11.56	127.06	
GW 2 TURLAK	2.16 11.49	129.22			
GW 1 TURLAK			2.084 11.566	127.136	
BM Turlak			4.94 8.71	124.28	✓

GW2



GW1



Benchmark



GW1



GW



GN



TURLAK GW1
ELEV. 127.13
DATE 8 24 11
BY EE MH
NAVD NGVD 29




TURLAK GW 2
ELEV. 127.06
DATE 8 24 11
BY EE MH
NAVD NGVD 29

06/28/11
D.W.



GW2
ASSUMED
REF. ELEV.
999 ft.
06/20/11
D.W.



GW2
ASSUMED
REF. ELEV.
999 FT.
06/20/11
D.W.

SOUTH FLORIDA WATER MANAGEMENT DISTRICT



Survey Data Entry and Retrieval Application (SDERA) Print Output

Control Point Search Results

Derived Data - Denoted By: **

Designation	TURLAK	Record State	ACCEPTED
NGS PID			
Project Name	TURKEY LAKE	Date Entered/Updated	11/06/2015
Updated By	hehmke	Status	RECOVERED
Party Chief		Type	H/V
Monument Set By	WOOLPERT INC	Date Established	01/22/2008
County	ORANGE COUNTY	Section	11
Township	23	Range	28
Quadrangle	ORLANDO WEST	Offset (29 to 88)	
NGS Source BM		CCR Link	
Ctrl Pt Source(s)			

Horizontal	NAD 1927	NAD 1983	Vertical	NGVD 1929	NAVD 1988
Latitude		28 30 02.9	Class		1
Longitude		81 28 36.0	Order	3	2
Northing(Y)		1515086.0	Elevation	124.28	123.39
Easting(X)		503067.0	Measurement Unit	Feet	Feet
Class					
Order					
NAD83 Adj Year					

Field Book
1

Field Book Pages
56-58

Stamping
TURLAK 2008

How to Reach
FROM THE INTERSECTION OF SR435 AND SR 526 IN ORLANDO, FL; TRAVEL SOUTH ON SR 435 FOR 0.70 MILES TO RALEIGH ST; TURN RIGHT (WEST) ONTO RALEIGH ST AND TRAVEL FOR 0.80 MILES TO SOUTH HIAWASSEE RD.; TURN LEFT (SOUTH) ONTO SOUTH HIAWASSEE RD AND GO 1.86 MILES TO TURKEY LAKE PARK ON THE WEST SIDE OF THE RD. (ASHLEY PARK COURT ON THE EAST SIDE); TURN LEFT (WEST) INTO TURKEY LAKE PARK AND FOLLOW ENTRANCE RD FOR ABOUT 0.60 MILES TO A PARKING AREA AND BUILDING; TURN RIGHT INTO PARKING AREA AND CONTINUE STRAIGHT TO THE ROAD ON THE SOUTHEAST SIDE OF PARKING LOT. BENCHMARK IS ON THE NORTH SIDE OF THE ROAD; 14.5 FEET FROM THE NORTH EDGE OF PVMT; 2.3 FEET NW OF AN EXISTING TELEMETRY ANTENNA POLE; 1.85 FEET WEST OF CARSONITE MARKER AND 5.7 FEET WEST OF CRW1.
NGS Source Benchmarks:
Gotha Reset (AK6868)
ORA30 (AA6655)

Description
SFWMD ALUMINUM DISK IN CONCRETE

DISCLAIMER:
The South Florida Water Management District (hereinafter referred to as the DISTRICT) shall

not be held liable for improper or incorrect use of the data, information, apparatus, products, processes or materials described and/or contained herein. These data, information, apparatus, products, processes, materials and related graphics are not legal documents and are not intended to be used as such. The user hereby recognizes that the information, data, apparatus, products, processes and materials are dynamic and may change over time without notice. However, the DISTRICT makes no commitment to update the information, data, apparatus, products, processes or materials contained herein.

SMURVEYR

