

Schlumberger

GEOFRAME PROCESSED INTERPRETATION

Porospect* Porosity Analysis Composite L

Processed FMI* Electrical Resistivity

* A Mark of Schlumberger

Using the following logs:

FMI*, UBJ*, DSI*
Platform Express*
HNQS*, AITH*

COMPANY: South Florida Water Management District
WELL: MF-37, St. Lucie Canal Site, (L-65-1)
FIELD: Port Mayaca Site
COUNTY:
STATE:
COUNTRY:
Date Logged: 24-Jul-2001 Date Processed: 2-Oct-2001
Well Location: Latitude: 26.59, 30.342°N
Longitude: 80.36, 15.883°W
Elevations: KB: DF: GL: 14.50 ft
API Number: Not Available Job Number:

FOLD HERE The well name, location, borehole reference data were furnished by the customer.

All interpretations are opinions based on inferences from electrical or other measurements and we cannot, and do not guarantee the accuracy or correctness of any interpretation, and we shall not, except in the case of gross or willful negligence on our part, be liable or responsible for any loss, costs, damages or expenses incurred or sustained by anyone resulting from any interpretations made by any of our officers, agents or employees. These interpretations are also subject to Clause 4 of our General Terms and Conditions as set out in our current Price Schedule.

Field Recording:	Location: Laurel	Software Version: 9C2-303	Engineer: S. Henley, C. Ertle
Office Recording:	ICS Center: IWS Denver	Baseline:	Log Analyst: N. Clayton

Mud and Borehole Measurements:

Rm @ Measured temperature: 5.580 ohm.m @ 32.0 degF	BHT: 75.0 degF	Bitsize: 7.9 in
Rmf @ Measured temperature: 4.185 ohm.m @ 70.0 degF	Type Fluid in Hole	Gel
Rmc @ Measured temperature: 8.370 ohm.m @ 70.0 degF	Mud Density: 9.50 lbm/gal	

Remarks:
Tool run as per tool sketch

